

# PPCC


Axial lead, Round  
Series

## Features

- Pure copper foil and polypropylene film capacitors
- mainly suitable for the high frequency divider
- Designed for the most transparent sound possible
- Copper foil is an additive sound! Big soundstage and fast!
- The OFC oxygen free copper pins
- Oxygen-free, non-inductive copper foil design with polypropylene dielectric



## 1) Dimensions:



## 2) Specifications:

- (1) Material : Pure copper foil and polypropylene film capacitors
- (2) Voltage rating : 100VDC, 250VDC, 400VDC, 630VDC
- (3) Capacitance tolerance :  $\pm 3\%$  or  $\pm 5\%$  at 1K HZ
- (4) Dissipation factor : MAX 0.1% at 1K Hz 25°C
- (5) Temperature range : -40°C ~ +85°C
- (6) Terminal leads are made from copper

## 3) MAX SIZE(D x L)

Unit : mm

| W.V.            | 100 VDC   |           | 250 VDC   |           | 400VDC    |           | 630VDC    |           |
|-----------------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|-----------|
| SIZE<br>CAP(F). | D $\pm 2$ | L $\pm 2$ | D $\pm 2$ | L $\pm 2$ | D $\pm 2$ | L $\pm 2$ | D $\pm 2$ | L $\pm 2$ |
| 0.10            | 16        | 40        | 16        | 40        | 16        | 40        | 16        | 40        |
| 0.22            | 16        | 40        | 18        | 40        | 20        | 40        | 20        | 40        |
| 0.33            | 18        | 40        | 20        | 40        | 22        | 40        | 22        | 40        |
| 0.47            | 20        | 40        | 22        | 40        | 26        | 40        | 26        | 40        |
| 0.56            | 20        | 40        | 22        | 40        | 26        | 40        | 26        | 40        |
| 0.68            | 22        | 40        | 22        | 40        | 26        | 40        | 26        | 40        |
| 1.0             | 22        | 50        | 22        | 50        | 26        | 50        | 26        | 50        |
| 1.5             | 22        | 50        | 26        | 50        | 30        | 50        | 30        | 50        |
| 2.2             | 26        | 60        | 26        | 60        | 26        | 60        | 26        | 60        |
| 3.3             | 30        | 60        | 30        | 60        | 30        | 60        | 30        | 60        |
| 4.7             | 35        | 60        | 35        | 60        | 38        | 60        | 38        | 60        |
| 5.6             | 35        | 60        | 38        | 60        | 42        | 60        | 42        | 60        |
| 6.8             | 38        | 60        | 42        | 60        | 46        | 60        |           |           |
| 8.2             | 42        | 60        | 46        | 60        | 50        | 60        |           |           |
| 10.0            | 46        | 60        | 51        | 60        | 55        | 60        |           |           |

ANY SPECIAL VALUE ARE ACCEPTABLE, ITS SIZE TO BE PROVIDED UPON REQUESTED  
SIZE MAYBE CHANGED W/O NOTICE. SPECIAL SIZE IS ACCEPTABLE

- 如有需特殊尺寸 / 容量-請洽本公司.
- 以上為參考尺寸,如有更動不另行通知.
- <https://WWW.MDL.COM.TW>