


PPCN

 Axial lead, Round
Series

Features

- Pure copper foil and polypropylene film capacitors
- mainly suitable for the high frequency divider
- Designed for the most transparent sound possible
- Copper foil is an addictive sound! Big soundstage and fast!
- The OFC oxygen free copper pins
- Oxygen-free, non-inductive copper foil design with polypropylene dielectric

1) Dimensions:



2) Specifications:

- (1) Material : Pure copper foil and polypropylene film capacitors
- (2) Voltage rating : 100VDC, 250VDC, 400VDC, 630VDC
- (3) Capacitance tolerance : $\pm 3\%$ or $\pm 5\%$ at 1K HZ
- (4) Dissipation factor : MAX 0.1% at 1K Hz 25°C
- (5) Temperature range : - 40°C ~ +85°C
- (6) Terminal leads are made from copper

3) MAX SIZE(D x L)

Unit : mm

W.V.	100 VDC		250 VDC		400VDC		630VDC	
SIZE CAP(μF).	D±2	L±2	D±2	L±2	D±2	L±2	D±2	L±2
0.10	12	35	13	35	14	35	15	35
0.22	14	35	16	35	17	35	18	35
0.33	16	35	18	35	18.5	35	19	35
0.47	18	35	21	35	21.5	35	22	35
0.56	17.5	40	19	40	20	40	21	40
0.68	19	40	20	40	22	40	23	40
1.0	18	45	20	45	22	45	24	45
1.5	21.5	45	25	45	26	45	27	45
2.2	22	55	22	55	26	55	28	55
3.3	26	55	28	55	31	55	33	55
4.7	30	55	33	55	36	55	38	55
5.6	32.5	55	36	55	40	55	42	55
6.8	35.5	55	39	55	43	55		
8.2	38.5	55	43	55	47	55		
10.0	42.5	55	49	55	52	55		

ANY SPECIAL VALUE ARE ACCEPTABLE, ITS SIZE TO BE PROVIDED UPON REQUESTED
SIZE MAYBE CHANGED W/O NOTICE. SPECIAL SIZE IS ACCEPTABLE

- 如有需特殊尺寸 / 容量-請洽本公司.
- 以上為參考尺寸,如有更動不另行通知.
- <https://WWW.MDL.COM.TW>

