


PPAC Axial lead, Round Series

Features

- Pure aluminum foil and polypropylene film capacitors
- mainly suitable for the high frequency divider

1) Dimensions:



2) Specifications:

- (1) Material : Pure aluminum foil and polypropylene film capacitors
- (2) Voltage rating : 100VDC, 250VDC, 400VDC, 630VDC
- (3) Capacitance tolerance : ±5% (J) at 1K HZ
- (4) Dissipation factor : MAX 0.1% at 1K Hz 25°C
- (5) Temperature range : -40°C ~ +85°C
- (6) Terminal leads are made from copper

3) MAX SIZE(D x L)

Unit : mm

| W.V. SIZE CAP(μF) | 100VDC | | 250 VDC | | 400 VDC | | 630 VDC | |
|-------------------------|--------|-----|---------|-----|---------|-----|---------|-----|
| | D±2 | L±2 | D±2 | L±2 | D±2 | L±2 | D±2 | L±2 |
| 0.10 | | | 16 | 45 | 16 | 45 | | |
| 0.22 | | | 16 | 45 | 18 | 45 | 18 | 45 |
| 0.33 | | | 18 | 45 | 20 | 45 | 20 | 45 |
| 0.47 | | | 20 | 45 | 22 | 45 | 22 | 45 |
| 1.0 | 18 | 50 | 20 | 50 | 20 | 50 | 20 | 50 |
| 1.5 | 20 | 50 | 22 | 50 | 26 | 50 | 26 | 50 |
| 2.2 | 22 | 50 | 26 | 50 | 30 | 50 | 30 | 50 |
| 3.3 | 26 | 50 | 30 | 50 | 35 | 50 | 35 | 50 |
| 4.0 | 28 | 50 | | | | | | |
| 4.7 | 30 | 50 | 35 | 50 | 38 | 50 | 38 | 50 |
| 5.6 | 35 | 50 | 36 | 50 | 42 | 50 | 42 | 50 |
| 6.0 | 35 | 50 | | | | | | |

ANY SPECIAL VALUE ARE ACCEPTABLE, ITS SIZE TO BE PROVIDED UPON REQUESTED
 SIZE MAYBE CHANGED W/O NOTICE. SPECIAL SIZE IS ACCEPTABLE

- 如有需特殊尺寸 / 容量-請洽本公司.
- 以上為參考尺寸,如有更動不另行通知.
- <https://WWW.MDL.COM.TW>